

Residential Series

INVERGY
UPGRADING POWER FOR BETTER FUTURE

OFF GRID INVERTER P+ SERIES – SINGLE PHASE

INV-OGH-1.5K-12V

INV-OGH-3.0K-24V

INV-OGH-4.0K-24V

INV-OGH-5.0K-48V

INV-OGH-6.0K-48V



-  Built-In Anti-Dust kit
-  Battery independent design
-  Built-in feed-in grid function
-  Built-in BMS communication port
-  Dual AC outputs (only for 4K/6K models)
-  Maximum charging current 100A/120A (based on models)
-  Wide PV input range (starts from 30VDC for 1.5K/3K/4K models)
-  Built-in WiFi with APP for remote monitoring and OTA firmware upgrade
-  Battery equalization function (optimize performance & extend lifecycle)

 Image may differ from the actual product.

 Toll Free NO. 1800 309 7880

 www.invergypowersupply.com

 ©2025 invergy India Pvt. Ltd. All rights reserved. Subject to change without notice. Version 1.1



Model	INV-OGH-1.5K-12V	INV-OGH-3.0K-24V	INV-OGH-4.0K-24V	INV-OGH-5.0K-48V	INV-OGH-6.0K-48V
Rated Power	1500VA/1500W	3000VA/3000W	4000VA/4000W	5000VA/5000W	6000VA/6000W
Input					
Voltage	230 VAC				
Selectable Voltage Range	170-280 VAC (For Personal Computers); 90-280 VAC (For Home Appliances)				
Frequency Range	50 Hz/60 Hz (Auto sensing)				
Output					
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%				
Output Power	1500W with PV & battery ; 1200W with battery only	3000W with PV & battery ; 2500W with battery only	4200W with PV & battery ; 4000W with battery only	6200W with PV & battery ; 5000W with battery only	
AC Output No.	Single D		Dual Outputs	Dual Outputs	
Surge Power	3000VA	6000VA	8400VA	12400VA	
Efficiency (Peak)	93%				
Transfer Time	10 ms (For Personal Computers); 20 ms (For Home Appliances)				
Waveform	Pure Sine Wave				
Battery					
Battery Voltage	12 VDC	24 VDC		48 VDC	
Floating Charge Voltage	13.5 VDC	27 VDC		54 VDC	
Overcharge Protection	16 VDC	32 VDC		63 VDC	
Solar Charger & AC Charger					
Solar Charger type	MPPT				
Maximum PV Array Open Circuit Voltage	350 VDC	450 VDC	500 VDC		
Maximum PV Array Power	2000W	3000W	5000W	6500W	
Maximum PV Input Current	13A		18A		
MPPT Range @ Operating Voltage	30 ~ 300 VDC (Min. 60VDC without battery connected)	30 ~ 400 VDC (Min. 60VDC without battery connected)	30 ~ 450 VDC (Min. 60VDC without battery connected)	90~450 VDC (Min. 100VDC without battery connected)	
Maximum Solar Charge Current	100A		120A	100A	
Maximum AC Charge Current	80A		100A		
Maximum Charge Current	100A		120A	100A	
Physical					
Dimension, D x W x H (mm)	90 x 288 x 357		90 x 288 x 357		
Net Weight (kgs)	6.6	7.1	9	10.4	
Communication Interface	RS232/RS485(BMS)/WiFi				
Operating Environment					
Humidity	5% to 95% Relative Humidity (Non-condensing)				
Operating Temperature	-10°C to 50°C				
Storage Temperature	-15°C to 60°C				